INVADO CATALOGUE EDITION 18

SINCE 1990



Open your dreams... and find your style

Today, we live in a constant rush, seeking peace, beauty, and a safe haven at home and in the places we visit. A sense of security and harmony significantly enhances our daily quality of life. At INVADO, we understand and respect these needs. As one of Poland's fastest-growing door joinery manufacturers, we strive to deliver products with exceptional aesthetics and outstanding usability. With over thirty years of experience, we build our market position through continuous investment in technology, people, and quality improvement.



OUALITY ABOVE ALL

The belief that quality is of the utmost importance remains the common denominator of the design phase and the entire production process at INVADO. This is confirmed, among others, by the ISO 9001 Certificate, which ensures that all our products meet high European standards. The guarantee of the quality of products and services, in addition to the price and timeliness of deliveries, is the basic goal of the company, enabling it to be perceived as a trusted partner.

INVADO TECHNOLOGY

The cornerstone of INVADO's offerings lies in the production of door leaves and frames. A significant milestone in the company's history was the introduction of an innovative technique in 2007 known as the "Pass-Through Foiling System for Flat Doors." This cutting-edge technology, used in INVADO flat doors, revolutionized the process by eliminating visible seams at the rebate edge. As a result, the edges not only boast a sleek, aesthetically pleasing finish but also offer enhanced durability. The veneer's connection is cleverly concealed within the inner edge of the rebate, preventing any risk of tearing or detachment. Today, INVADO stands as one of Europe's most technologically advanced companies, thanks to this pioneering approach to door manufacturing.

HYGIENIC CERTIFICATES

Hygienic certifications aim to prevent materials and products hazardous to health and life to be introduced to the public or limit the acceptable range and application methods to eliminate health risks. All INVADO products have hygienic certificates:

· interior door leaves in artificial veneer or flat lacquered No. 348/322/353/2020

TECHNICAL APPROVALS AND NATIONAL TECHNICAL **ASSESSMENTS**

Technical Approvals and National Technical Assessments, issued by the Building Research Institute, are decisions that grant the use of building materials and products. In accordance with the Conpuction Products Act of April 16th 2004, as amended (unified text: Journal of Laws of 2016, item 1570), the products to which the Technical Approvals and National Technical Assessments relate, may be placed on the market and can be used in conpuction. INVADO Company assessed and verified the constancy of performance, made a national declaration of performance, and labeled the products with a conpuction mark in accordance with applicable regulations. INVADO's Technical Approvals and National Technical Assessments:

- Interior flat and glass doors—ITB-KOT-2017/0313 edition 2;
- Modular interior doors—ITB-KOT-2017/0003 edition 2;
- Adjustable door frames for interior doors—ITB-KOT-2019/1221 edition 2;
- Block door frames for interior doors OB3 type P—ITB-KOT-2017/0312 edition 2:
- Metal door frames—ITB-KOT-2021/2091 edition 1;
- Housing system for metal door frames—ITB-KOT-2019/1221 edition 2.





Once again this year, the INVADO brand has been recognized by Polish consumers and honored with the prestigious Consumer Laurel ODKRYCIE 2024 award.

BRAND OF THE DECADE 2009-2019; GOOD BRAND 2019 AND 2021





An independent group of experts confirmed that products bearing the INVADO logo are characterized by: quality, trust, and reputation, awarding our company the title of BRAND OF THE DECADE 2009–2019 and the titles of GOOD BRAND 2019 and GOOD BRAND 2021. We would like to thank our customers for the trust you place in us by choosing INVADO doors for their dream interiors, our Business Partners for fruitful cooperation, recommending, and support, and all INVADO Employees for jointly building a good brand at every stage of its creation. We are incredibly grateful that our hard work is appreciated and we look forward to the future with pride.



VOC

The VOC certification tests the emission of volatile organic compounds released from the facility and, depending on the results obtained, the tested sample is assigned

a class, ranging from A+ (best) to C (worst). The possession of the VOC certificate confirms that the product does not release harmful to health substances inside the house, such as formaldehyde and benzene—carcinogenic elements that unfortunately are often contained in paints, and materials used on windows.



ISO 9001

ISO 9001

The INVADO Company applies to the Quality Management System and fulfills the requirements of PN-EN ISO 9001 in the scope of designing, production, and sale of furniture components and finishing profiles, interior doors made of wood and wood-based materials, and technical doors.



FSC®

Control of Product Origin and environmental protection are the leading elements of INVADO's development pategy. This is confirmed by an international certificate issued by the Forest Stewardship Council® and obtained by the company in 2007.

Ask for FSC® certified products in our range.



CERTIFICATE RESOURCES SAVED

INVADO has obtained the international certificate in waste management and recycling issued by INTERSEROH zero waste solutions.













Table of contents

GOOD TO KNOW	7
GLASSTYPES	9
DECOR PALETTE	10
COLLECTION OF MODULAR DOORS	12
COLLECTION OF FOILED DOORS	58
COLLECTION OF GLASS DOORS	96
COLLECTION OF FOLDING DOORS	98
SLIDING SYSTEMS	
POCKET DOOR sliding system	100
WALL-MOUNTED sliding system	102
TECHNICAL INFORMATION	104
DOOR FRAMES	
BLOCK door frame	106
ADJUSTABLE door frame (REBATED)	108
ADJUSTABLE door frame (NON-REBATED)	110
METAL door frames	112
Concealed door frame SARA-PRO	114
Housing system for metal door frames	116
ACCESSORIES	117
HANDLES	120
SKIRTINGS	122







COLLECTION OF MODULAR DOORS



COLLECTION OF FOILED DOORS







FOILED AND MODULAR DOORS

FOILED DOORS

Foiled doors appear visually lighter than modular doors. They feature an MDF frame with a filling of either 'honeycomb' or chipboard, available at an additional cost. The frame and infill are covered on both sides with 3 mm thick HDF and decorative foil. Glazing beads are used to secure the infills in these models.



MODULAR DOORS

The construction of **modular doors** consists of two vertical frames and an upper and lower frame. The leaf can be filled with panels or glass of varying thicknesses. Each model can be customized with a decorative foil. Unlike traditional methods, the panes and other fillings in these doors are mounted simultaneously with the door construction elements, significantly enhancing their stability.



REBATED AND NON-REBATED DOORS



REBATED DOORS

The edge of a **rebated door** is finished with a rim (Fig. 1) that overlaps the frame. This design ensures that the door does not sit flush with the frame.




NON-REBATED DOORS

The edge of a **non-rebated door** is a smooth, uniform plane. Doors constructed this way align with the frame on the hinge side (Fig. 2)

LEFT AND RIGHT DOOR

Before buying doors, it is worth considering in which direction they should open. For safety reasons, bathroom or kitchen doors should be installed in a way that makes it possible to open them outwards. In other areas, it is dependent on users' preference and the layout of the apartment or house.

The next step is to determine whether you need a right-hand or left-hand door. How can you tell? If the hinges are on the right side of the door frame, you'll need a right-hand door, if they're on the left, you'll need a left-hand door. It's important to consider this carefully before heading to the store. Make a list of the right-hand and left-hand doors you need, along with the opening direction for each one.



RIGHT DOOR



DOOR PRICE CALCULATION

In most cases, the quoted prices are for a door leaf without a door frame and door handles. To obtain the full price of the door set, you have to use the following calculation:



LEGEND

Please note the annotations marked with the following icons. They contain important information related to the door leaf models.




















SATINATO



CHINCHILLA



TRANSPARENT



LACOBEL



SATINATO WITH ENGRAVING



ENDURO ••000

ENDURO classification: a foil with high design value and excellent reproduction of the natural wood grain. It is characterized by its good durability properties.



ENDURO 3D ••000

ENDURO 3D classification: three-dimensional reproduction of the wood structure and good durability.



ENDURO PLUS ••000

ENDURO PLUS classification: a group of foils with high design value, noticeable texture, and good durability.






ECO-VENEER ••••

ECO-VENEER classification: high-quality laminate in modern colours, very high durability.



LAMINOLACK

Classification LAMINOLACK: high-quality polypropylene foil is characterised by excellent durability.



LAMINATE CPL 0.15 mm •••• 0.8 mm ••••

Classification CPL: Foils with maximum strength. Available in two thicknesses – 0.15 mm (door leaves and frames) and 0.8 mm (door leaves).



11

COLLECTION OF MODULAR DOORS





Vista



DOOR LEAVES OPTIONS





















Bolection only in black

the filling element (depending on the model):

- hardened glass:
- satinato 4 mm • transparent – 4 mm
- 2 MDF bolections
- 3 horizontal frame – MDF
- 4 vertical frame – MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"
- bolection only in black

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







TRANSPARENT





flagstaff oak

catania oak

narbonne oak



DECORS ENDURO PLUS · · ENDURO ·· ENDURO 3D ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra snowy oak winter oak cedar forte naturo oak ECO-VENEER ··· LAMINOLACK · · · · B739 B770

pure green

pure graphite

pure black

pure light-grey

pure white

pure cashmire

eterno oak

grey oak

white



Gavi 1









CONSTRUCTION

the filling element (depending on the model): hardened glass – 4 mm Lacobel glass – 4 mm panel – 4 mm



- horizontal frame MDF (height: lower frame 400 mm, upper frame 350 mm)
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







LACOBEL





ENDURO PLUS ·· ENDURO ·· ENDURO 3D ·· autumn oak european oak scandinavian oak karlstad oak anthracite classic walnut precious oak siberian larch spring oak coimbra ashy oak snowy oak winter oak cedar forte naturo oak ECO-VENEER ··· LAMINOLACK · · · · B739 B770 B474 pure graphite white eterno oak pure white pure cashmire pure light-grey pure black narbonne oak flagstaff oak catania oak grey oak pure green

DECORS















the filling element (depending on the model): tempered glass – 4 mm panel – 4 mm

panel – 4 mm black matt

2 filling element: panel – 22 mm

horizontal frame – MDF (height: lower frame 400 mm, upper frame 350 mm)

4 vertical frame – MDF

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112















- the filling element (depending on the model): tempered glass – 4 mm panel – 4 mm
- 2 filling element: panel 16 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







ENDURO 3D ·· ENDURO PLUS · · ENDURO ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra snowy oak winter oak cedar forte naturo oak ECO-VENEER ··· LAMINOLACK · · · · B739 B770 B474 flagstaff oak white pure white eterno oak pure cashmire pure light-grey pure graphite pure black narbonne oak catania oak grey oak pure green

DECORS









the filling element (depending on the model): tempered glass – 4 mm panel – 4 mm

panel – 4 mm black matt

2 filling element: panel – 16 mm

3 horizontal frame – MDF

4 vertical frame – MDF

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80",
3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
$\cite{[ORS4]}$ adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112



Mirror



DOOR LEAVES OPTIONS















- filling element: mirror 4 mm
- 2 filling element: panel 6 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF

side edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

pa	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
$\hbox{[ORS4]}$ adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC


sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

















the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm



horizontal frame – MDF (height: lower frame 400 mm, upper frame 350 mm)

4 vertical frame – MDF

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves me

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

















the filling element (depending on the model): 1 hardened glass – 4 mm panel – 4 mm

filling element: panel – 22 mm

3 horizontal frame – MDF

4 vertical frame – MDF

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)


Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







ENDURO 3D ·· ENDURO PLUS · · ENDURO ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak naturo oak coimbra snowy oak winter oak cedar forte ECO-VENEER ··· LAMINOLACK · · · · B739 B770 flagstaff oak pure white white grey oak eterno oak pure cashmire pure light-grey pure graphite pure black narbonne oak catania oak pure green

DECORS















the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm



- 3 horizontal frame MDF
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyho	حاد

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112



Imperia



DOOR LEAVES OPTIONS



ENDURO 3D ·· ENDURO PLUS ·· ENDURO ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra snowy oak winter oak cedar forte ECO-VENEER ··· LAMINOLACK · · · · B739 B770 flagstaff oak white grey oak eterno oak pure white pure cashmire pure light-grey pure graphite pure black narbonne oak catania oak pure green

DECORS











the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm

- 2 filling element: panel 22 mm
- horizontal frame MDF (height: lower frame 400 mm, upper frame 350 mm)
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)


Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







ENDURO PLUS ·· ENDURO ·· ENDURO 3D ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra snowy oak winter oak cedar forte ECO-VENEER ··· LAMINOLACK · · · · B739 B770 pure graphite pure black white eterno oak pure white pure cashmire pure light-grey narbonne oak flagstaff oak catania oak grey oak pure green

DECORS













- the filling element (depending on the model):

 1 hardened glass 4 mm
 panel 4 mm
- 2 filling element: panel 22 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- 5 inlay Lacobel glass
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

hidden hinges with a 3D regulation in satin chrome

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 \times 60 mm or 16 \times 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door withou	ıt a k	lodva	_

door width "100"

door made in non-rebated version

double door

sliding door

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

GLASS







RAL 7015 RAL 9005 RAL 9005 soft

















the filling element (depending on the model): 1 hardened glass – 4 mm panel – 4 mm

2 filling element: panel – 22 mm

3 horizontal frame – MDF

4 vertical frame – MDF

• side edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80",
3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)


Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







ENDURO 3D ·· ENDURO PLUS · · ENDURO ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra snowy oak winter oak cedar forte ECO-VENEER ··· LAMINOLACK · · · · B739 B770 pure graphite pure black flagstaff oak white eterno oak pure white pure cashmire pure light-grey narbonne oak catania oak grey oak pure green















the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm

2 filling element: panel – 22 mm

horizontal frame – MDF (height: lower frame 400 mm, upper frame 350 mm)

4 vertical frame – MDF

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

ted	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112



















the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm

filling element: panel – 22 mm

3 horzontal frame – MDF

4 vertical frame – MDF

- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

ted	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
ion-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112



Tamparo



DOOR LEAVES OPTIONS

flagstaff oak

catania oak

narbonne oak



pure green

pure graphite

pure black

pure light-grey

white

grey oak

eterno oak

pure white

pure cashmire











the filling element (depending on the model):
hardened glass – 4 mm
panel – 4 mm
panel – 4 mm black matt

2 filling element: panel – 22 mm

3 horizontal frame – MDF

4 vertical frame – MDF

• side edges and upper edge are foiled

- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112





rounded edge non-rebated rebated 60–100 120–200 sliding systems with ventilation



















the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm panel – 4 mm black matt B726

2 filling element: panel – 22 mm

horizontal frame – MDF (height: lower frame 400 mm, upper frame 350 mm)

- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

	rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
		screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
	non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
		milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

	[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
	[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
	[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
	[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
	[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
	$\left[\text{ORS4}\right]$ adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
	NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







ENDURO 3D ·· ENDURO PLUS ·· ENDURO ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra winter oak cedar forte ECO-VENEER ··· LAMINOLACK · · · · B739 pure black flagstaff oak eterno oak pure white pure cashmire pure light-grey pure graphite narbonne oak catania oak grey oak pure green













- the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm
- 2 filling element: panel 22 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- 5 insert 8 mm aluminium strip
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100" / width of double doors: "120"-"200"
- aluminium insert protrudes above the leaf surface

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

P\/C

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)


Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112





rounded edge non-rebated rebated 60–100 120–200 sliding systems with ventilati

DECORS ENDURO 3D ·· ENDURO PLUS · · ENDURO ·· autumn oak european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak siberian larch spring oak coimbra snowy oak winter oak cedar forte ECO-VENEER ··· LAMINOLACK · · · · B739 B770 flagstaff oak pure white white eterno oak pure cashmire pure light-grey pure graphite pure black narbonne oak catania oak grey oak pure green













- the filling element (depending on the model): hardened glass – 4 mm panel – 4 mm
- 2 filling element: panel 22 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

ted	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
rebated	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles


PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112



Domino



DOOR LEAVES OPTIONS















the filling element (depending on the model): hardened glass:

- satinato 4 mm
- transparent 4 mm (Domino 2 only)
- 2 filling element: panel 10 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112







TRANSPARENT


























- the filling element (depending on the model): 1 hardened glass – 4 mm panel – 10 mm
- 2 filling element: panel 33 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90" and "100"
ion-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole	
door width "100"	

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"–"80" $\,$

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
$\hbox{[ORS4]}$ adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112













Larina NUBE























CONSTRUCTION

the filling element (depending on the model): 1 hardened glass – 4 mm panel – 10 mm

- 2 filling element: panel 35 mm
- 3 horizontal frame MDF
- 4 vertical frame MDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

10011011



STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert	
	reba	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
bated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert	
non-rebated		milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112



D'Artagnan



DOOR LEAVES OPTIONS



ENDURO ·· ENDURO 3D ·· ENDURO PLUS ·· ECO-VENEER ··· B402 white coimbra autumn oak scandinavian oak karlstad oak precious oak siberian larch spring oak winter oak grey oak eterno oak









the filling element (depending on the model): hardened glass – 6 mm panel – 10 mm



- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"100"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90" and "100"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-re	milling for hidden hinges with a 3D regulation

ADDITIONAL OPTIONS

door without a keyhole

door width "100"

door made in non-rebated version

double door

additional hinge for the door in sizes "60"-"80"

additional hinge for the non-rebated door—included in a door frame

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut (ONLY FOR THE INTERO MODEL)

cylinder lock insert 31/36 (31/31 in non-rebated door leaves)

Additional information: accessories and handles

PAGE 118

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
$\cite{[ORS4]}$ adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

GLASS







TRANSPARENT




ENGRAVING 7 TONDO only

longer execution time

FOILED DOORS

Foiled doors, with their MDF frame construction, are significantly lighter than modular doors while maintaining high strength. Our collection offers a wide range of models featuring both modern and timeless designs at attractive prices. These doors are perfect for those looking to completely transform their interiors.







ENDURO : ENDURO 3D . ENDURO PLUS . B708 B134 B224 B706 B339 B707 B708

european oak

spring oak

DECORS

lindo (white)









- the frame is made of an MDF board
- 2 (STANDARD)
 "honeycomb" filling
- 3 (OPTIONAL) tubular chipboard filling
- 4 HDF
- side edges and upper edge are foiled
- cut edges (90°) of door leaf (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding door

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

ventilation grid

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118























- the frame is made of an MDF board
- 2 (STANDARD)
 "honeycomb" filling
- 3 (OPTIONAL) tubular chipboard filling
- 4 HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110" / width of double doors: "120"-"200"
- non-rebated leaves only with the cut-edge



rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90"—"110"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
non-t	milling for hidden hinges with a 3D regulation

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

GLASS







SATINATO the glossy side of glass is on the hinge side

ADDITIONAL OPTIONS

door	without	a ke	vhole

door width "100"; "110"

door made in non-rebated version

double door

sliding leaf

tubular chipboard filling

cylinder lock insert 31/36

additional hinge for the door in sizes "60" – "80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

additional hinge for the non-rebated door—included in a door frame
cylinder lock insert 31/31

ventilation undercut

PVC
metal, round (chrome, golden)
metal, square (chrome, nickel)

ventilation grid

reinforcement for self-closer

Additional information: accessories and handles

PAGE 118



Porthole in NORMA DECOR 6 available in silver and black colour with the possibility of using a transparent or satin glass pane (option included in the price of the door leaf).



TRANSPARENT ND6 only















Due to the manufacturing technique, for doors from the OPTIMO LINE collection, it is possible to use the edge of the leaf in a different colour than its surface. The base for creating unique creations is the edge in the colour: pure black, alpine white, or natural Hamilton oak in combination with the OPTIMO LINE colour palette (p. 119)

CONSTRUCTION

- 1 the frame is made of an MDF board
- 2 (STANDARD)
 "honeycomb" filling
- 3 (OPTIONAL) tubular chipboard filling
- 4 HDF
- · side edges and upper edge are foiled
- · edge band in the colour of the door leaf
- cut edges (90°) of door leaf (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"—"110" / width of double doors: "120"—"200'
- In double non-rebated door leaves, edge band in the colour of the door leaf and silver fittings are standard. However, it is possible to make them with pure black edge band and fittings as part of a custom order. In this case, please contact our Customer Service.

STANDARD EOUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"—"80", 3 pcs for door leaves in sizes "90"—"110"

magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert

milling for hidden hinges with a 3D regulation

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door	without	2	kaybal	_

door width "100"; "110"— CPL 0.15 mm

door width "100"; "110"— CPL 0.8 mm

cylinder lock insert 31/36

cylinder lock insert 31/31

door made in non-rebated version

double door

sliding leaf

tubular chipboard filling

oated

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

additional hinge for the non-rebated door—included in a door frame

non-rebated

pure black or alpine white edge band

natural hamilton oak edge band (only in alpine white door leaf)

a set of: 2 hinges + striking plate + door lock in colours: white, satin chrome, golden, black

ventilation undercut PVC

eeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

ventilation grid

reinforcement for self-closer


Additional information: accessories and handles

PAGE 118

Porthole in OPTIMO LINE 6 available in silver and black colour with the possibility of using a transparent or satin glass pane (option included in the price of the door leaf).



Vetra ----



DOOR LEAVES OPTIONS



















- 1 the frame is made of an MDF board
- 2 (STANDARD) tubular chipboard filling
- 3 HDF
- inlay: Lacobel glass flush with the leaf surface
- side edges and upper edge are **foiled**
- cut edges (90°) of door leaf (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60" "110" / width of double doors: "120" "200"
- Lacobel glass inlay is flush with the leaf surface

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert $$
	milling for hidden hinges with a 3D regulation

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10×60 mm or 16×80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a ke	eyhole		
door width "100";	door width "100"; "110"		
door made in no	n-rebated version		
double door			
sliding leaf			
	cylinder lock insert 31/36		
rebated	additional hinge for the door in sizes "60" – "80"		
	caps for hinges (chrome, satin chrome, golden, black, white) 1 hinge unit	—set for	
non-rebated	additional hinge for the non-rebated door—included in a do	oor frame	
non-repated	cylinder lock insert 31/36		
ventilation under	rcut		
Additional inform	nation: accessories and handles	PAGE 118	

GLASS INLAY

















- the frame is made of an MDF board
- (STANDARD) tubular chipboard filling
- HDF
- insert: aluminium strip—8 mm
- side edges and upper edge are $\ensuremath{\text{foiled}}$
- cut edges (90°) of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"–"110"/ width of double doors: "120"–"200"
- aluminium inlay is flush with the leaf surface

STANDARD EQUIPMENT

rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"
non-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	milling for hidden hinges with a 3D regulation

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10×60 mm or 16×80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole			
door width "100";"	door width "100"; "110"		
door made in non-	rebated version		
double door			
sliding leaf			
	cylinder lock insert 31/36		
rebated	additional hinge for the door in sizes "60" – "80"		
	caps for hinges (chrome, satin chrome, golden, black, white 1 hinge unit	e)—set for	
non-rebated	additional hinge for the non-rebated door—included in a	door frame	
non-repated	cylinder lock insert 31/36		
ventilation underc	ut		
Additional informa	tion: accessories and handles	PAGE 118	





































AVAILABLE ONLY AS SINGLE DOORS

- the frame is made of an MDF board
- 2 (STANDARD)
 "honeycomb" filling
- 3 (OPTIONAL) tubular chipboard filling
- 4 black HDF
- 5 black milling—"U" with a width of 8 mm
- side edges and upper edge are foiled
- edge band in the colour of the door leaf (standard) or black (optional)
- cut edges (90°) of door leaf (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT


rebated	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"
on-rebated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert $$
	milling for hidden hinges with a 3D regulation


DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10×60 mm or 16×80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS


door without a keyhole		
door width "100"; "110"		
door made in non-	rebated version	
double door		
sliding leaf		
tubular chipboard filling		
rebated	cylinder lock insert 31/36	
	additional hinge for the door in sizes "60" – "80"	
	caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit	
non-rebated	additional hinge for the non-rebated door—included in a	door frame
	cylinder lock insert 31/31	
ventilation underco	ut	
reinforcement for s	self-closer	
black edge band		
Additional information: accessories and handles PAGE		PAGE 118











- 1 the frame is made of an MDF board
- 2 (STANDARD) "honeycomb" filling
- 3 (OPTIONAL) tubular chipboard filling
- 4 black HDF
- 5 black milling—"V" with a width of 3 mm
- side edges and upper edge are foiled
- edge band in the colour of the door leaf (standard) or black (optional)
- cut edges (90°) of door leaf (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT


on-rebated rebated	ited	lock 72 mm for a standard key, a WC knob, or a cylinder lock insert
	reba	screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"
	sbated	magnetic lock 90 mm for a standard key, 95 mm for a WC knob, and 85 mm for a cylinder lock insert
	on-r	milling for hidden hinges with a 3D regulation

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10×60 mm or 16×80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
[ORS7] adjustable door frame for modular non-rebated doors with a flat angle architrave 60 mm-wide	P. 110
[ORS10] adjustable door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
[ORS4] adjustable 90° door frame for modular non-rebated doors with a flat angle architrave 80 mm-wide	P. 110
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole		
door width "100", "110"		
door made in non-	rebated version	
double door		
sliding leaf		
tubular chipboard f	filling	
	cylinder lock insert 31/36	
rebated	additional hinge for the door in sizes "60" – "80"	
	caps for hinges (chrome, satin chrome, golden, black, white 1 hinge unit	:)—set for
non robated	additional hinge for the non-rebated door—included in a c	door frame
non-rebated cylinder lock insert 31/31		
ventilation undercu	ut	
reinforcement for self-closer		
black edge band		
Additional information: accessories and handles PAGE 118		

















- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- HDF
- side edges and upper edge are **foiled**
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118



Gemini



DOOR LEAVES OPTIONS













- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)


cylinder lock insert 31/36


Additional information: accessories and handles

PAGE 118















- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- - HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118



Lido

Rebated Lido 14 in **B134**



DOOR LEAVES OPTIONS









- the frame is made of an MDF board
- 2 (STANDARD) tubular chipboard filling
- 3 HDF
- 4 insert: aluminium strip—8 mm
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110" / width of double doors: "120"-"200"
- aluminum insert protrudes above the surface of the door leaf

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert $\,$

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC


sleeves metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118





white

grey oak

eterno oak

DECORS ENDURO ·· ENDURO 3D ·· B134 B402 lindo (white) oak autumn oak walnut european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak coimbra beech ENDURO PLUS ·· ECO-VENEER ···

cedar forte

naturo oak

winter oak

siberian larch

spring oak

snowy oak













- 1 the frame is made of an MDF board
- 2 (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- 4 HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

sbated

80 mm-wide

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert $\,$

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm) P. 106 [ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide [ORS8] adjustable door frame for rebated doors with a flat angle architrave P. 108

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118

GLASS

P. 112







CHINCHILLA





















- the frame is made of an MDF board
- 2 (STANDARD)
 "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- 4 HDF
- + 1101
- side edges and upper edge are **foiled**
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

ated

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118







white

grey oak

eterno oak

DECORS ENDURO ·· ENDURO 3D ·· B134 B402 lindo (white) oak autumn oak walnut european oak scandinavian oak karlstad oak ashy oak classic walnut precious oak coimbra beech anthracite ENDURO PLUS ·· ECO-VENEER ··· B708 B705 B490

cedar forte

naturo oak

winter oak

siberian larch

spring oak

snowy oak









- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118

















- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- HDF
- side edges and upper edge are ${\bf foiled}$
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"–"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118



















- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110"/ width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)


cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118



Strada collection of foiled doors



DOOR LEAVES OPTIONS



DECORS ENDURO ·· ENDURO 3D ·· B134 B402 lindo (white) coimbra beech oak autumn oak walnut european oak scandinavian oak karlstad oak ashy oak anthracite classic walnut precious oak ENDURO PLUS ·· ECO-VENEER ··· siberian larch cedar forte white spring oak snowy oak winter oak naturo oak grey oak eterno oak









- the frame is made of an MDF board
- 2 (STANDARD)
 "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- 4 HDF
- וטוו
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

ebated

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert $\,$

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118



















- the frame is made of an MDF board
- (STANDARD) "honeycomb" filling
- (OPTIONAL) tubular chipboard filling
- HDF
- side edges and upper edge are foiled
- rounded vertical edges of door leaves (more info on p. 104)
- double door leaves have a rebate and a counter-rebate (drawing on p. 104)
- width of single doors: "60"-"110" / width of double doors: "120"-"200"

STANDARD EQUIPMENT

lock 72 mm for a standard key, a WC knob, or a cylinder lock insert

screw-in pivot hinges 13.5/9 (white zinc)—2 pcs for door leaves in sizes "60"–"80", 3 pcs for door leaves in sizes "90"–"110"

DEDICATED DOOR FRAMES

[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108
NOTE: THE OFFER ALSO INCLUDES METAL DOOR FRAMES	P. 112

ADDITIONAL OPTIONS

door without a keyhole

door width "100"; "110"

double door

sliding leaf

tubular chipboard filling

additional hinge for the door in sizes "60"-"80"

caps for hinges (chrome, satin chrome, golden, black, white)—set for 1 hinge unit

ventilation undercut

PVC

sleeves

metal, round (chrome, golden)

metal, square (chrome, nickel)

cylinder lock insert 31/36

Additional information: accessories and handles

PAGE 118



Amber



LOCK COLOURS



anodized silver





DOOR LEAVES OPTIONS





LOCKS

















GROUP I







GROUP II

Amber doors are divided into groups due to the types of glass decorations:

GROUP I—basic glass (transparent or matte in various shades) Amber 13—satinato glass

Amber 14—transparent glass

Amber 15—satinato glass

GROUP II—decorated glass (engraving or overprint)

Amber 3—overprint on transparent glass

Amber 6—overprint on transparent glass

Amber 12—engraving on satinato glass

CONSTRUCTION

- tempered glass, 8 mm thick
- the matt side of a glass pane is on the hinge side
- block or adjustable door frame, 2 hinges

DEDICATED DOOR FRAMES


[OB3] block door frame (possibility to add an architrave 10×60 mm or 16×80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108

DIMENSIONS OF GLASS DOORS (MM)

	"60"	"70"	"80"	"90"				
door leaf width	617	717	817	917				
door leaf height	(PL) 2027/1975 (CZ-SK)							

ADDITIONAL OPTIONS

ventilation undercut


















- MDF frame
- (STANDARD) 'honeycomb' filling
- HDF



- the top track for folding doors comes with a frame specifically designed for the $\,$ folding door leaf.
- folding doors are supplied as a universal leaf (for left or right-hand installation)
- folding doors consist of two narrow leaves connected by recessed hinges
- folding doors are mounted bottom to floor and top to track
- width of single doors: "60"-"90"

STANDARD EQUIPMENT

- silver round grip in colour satin chrome
- 2 hidden hinges in colour satin chrome

DEDICATED DOOR FRAMES


[OB3] block door frame (possibility to add an architrave 10 x 60 mm or 16 x 80 mm)	P. 106
[ORS1] adjustable door frame for rebated doors with a flat angle architrave 60 mm-wide	P. 108
[ORS8] adjustable door frame for rebated doors with a flat angle architrave 80 mm-wide	P. 108





Pocket door sliding system

SLIDING SYSTEMS



SYSTEM ELEMENTS

construction cassette for the sliding system in sizes "100" or "125"

set of profiles (door frame), brushes and seals

set of covering profiles for both sides of the door frame

ADDITIONAL OPTIONS

soft-close hardware for sliding door

key hook lock or WC hook lock (chrome, satin, golden, black) with a grip suitable for key or WC lock. In case of door leaves equipped with a hook lock, the customer installs the striking plate in the door frame on their own

key WC

extension (tunnel) to increase the regulation range of the frame (price for every 10 mm started). The minimum width of the extension is 20 mm


strike plate


The cassette with thickness 100 mm is designed for modular door leaves (eg. Domino, Versano, Tamparo) and standard flat doors.

The cassette with thickness 125 mm is designed for standard foiled door leaves (eg Parma, Strada).




DIAGRAM OF THE LOCATION OF DOOR FRAME ELEMENTS FOR SLIDING SYSTEM—SINGLE SLIDING SYSTEM






DIMENSIONS OF THE CA	DOOR LEAI	F DIMENS	IONS (mm)				
internal width L x H	outer width C x H1	А	В	wall thickness	width	height	
610 x 2010 (PL)/1955 (CZ-SK)	1346 x 2120 (PL)/2065 (CZ-SK)	670	640		644		
710 x 2010 (PL)/1955 (CZ-SK)	1546 x 2120 (PL)/2065 (CZ-SK)	770	740		744	2040 (PL)	
810 x 2010 (PL)/1955 (CZ-SK)	1746 x 2120(PL)/2065 (CZ-SK)	870	840	100-125	844	/ 1988	
910 x 2010 (PL)/1955 (CZ-SK)	1946 x 2120 (PL)/2065 (CZ-SK)	970	940		944	(CZ-SK)	
1010 x 2010 (PL)/1955 (CZ-SK)	2146 x 2120 (PL)/2065 (CZ-SK)	1070	1040		1044		
H—internal height of the cassette; H1—outer height; L—internal width; C—outer width.							


DIAGRAM OF THE LOCATION OF DOOR FRAME ELEMENTS FOR SLIDING SYSTEM—DOUBLE SLIDING SYSTEM






TONDOO							
internal width L x H	outer width C x H1	А	В	wall thickness	width	height	
1224 x 2010 (PL)/1955 (CZ-SK)	2610 x 2120 (PL)/2065 (CZ-SK)	1290	640		644		
1424 x 2010 (PL)/1955 (CZ-SK)	3010 x 2120 (PL)/2065 (CZ-SK)	1490	740		744	2040 (PL)	
1624 x 2010 (PL)/1955 (CZ-SK)	3410 x 2120 (PL)/2065 (CZ-SK)	1690	840	100-125	844	/ 1988	
1824 x 2010 (PL)/1955 (CZ-SK)	3810 x 2120 (PL)/2065 (CZ-SK)	1890	940		944	(CZ-SK)	
2024 x 2010 (PL)/1955 (CZ-SK)	4210 x 2120 (PL)/2065 (CZ-SK)	2090	1040		1044		
H—internal height of the cassette; H1—outer height; L—internal width; C—outer width.							

DIAGRAM OF THE LOCATION OF DOOR FRAME ENLARGING ELEMENTS FOR THE POCKET DOOR SLIDING SYSTEM



CASETTE ENCLOSURE ELEMENTS

A—upper profle + angle architrave; **B**—vertical profle + angle architrave; **C**—fender beam + angle architrave





Mr. St.







strike plate

door seal

profiles and architraves

brush

soft-close hardware for sliding door

Wall-mounted sliding system

SLIDING SYSTEMS



SYSTEM ELEMENTS

rail	200 cm rail mounted on aluminium angle bracket
curtain rod	curtain rod in the colour of the door leaf – mounted on an aluminium rail (two types depending on the height of the back band used in the door frame – ORS3] 60 mm or [ORS9] 80 mm)

ADDITIONAL OPTIONS AT EXTRA CHARGE

soft-close hardware for sliding door


orxWC lock	WC
key hook lock or WC hook lock (chrome, satin, golden, black) with a grip suitable for key	KEY
	CPL 0.15 mm
bumper	ECO-VENEER/LAMINOLACK
	ENDURO/PLUS/3D




DIMENSIONS OF THE DOOR LEAF AND THE DOOR FRAME FOR THE WALL-MOUNTED SLIDING SYSTEM

				door frame for single door (mm)				door frame for double door (mm)								
			"60"	"70"	"80"	"90"	"100"	"120"	"130"	"140"	"150	"160"	"170"	"180"	"190"	"200"
s1		door leaf width	644	744	844	944	1044	1288	1388	1488	1588	1688	1788	1888	1988	2088
s2	width of t	he wall opening*	674	774	874	974	1074	1310	1410	1510	1610	1710	1810	1910	2010	2110
s3	outer width	of the door frame	644	744	844	944	1044	1280	1380	1480	1580	1680	1780	1880	1980	2080
s4	internal width	of the door frame	600	700	800	900	1000	1236	1336	1436	1536	1636	1736	1836	1936	2036
۰.۵	width of the	60 mm [ORS3]	744	844	944	1044	1144	1380	1480	1580	1680	1780	1880	1980	2080	2180
s5	door frame with architraves	80 mm [ORS9]	784	884	984	1084	1184	1420	1520	1620	1720	1820	1920	2020	2120	2220
h1		door leaf height						20	040 (PL) /19	988 (CZ-SK	()					
h2	height of	the wall opening						20)62 (PL) /20	008 (CZ-SK	()					
h3	outer height o	of the door frame		2047 (PL) /1993 (CZ-SK)												
h4	internal height o	f the door frame*	2025 (PL) /1971 (CZ-SK)													
h.r.	height of the	60 mm [ORS3]						20)97 (PL) /20	043 (CZ-SK	()					
h5	door frame with architraves	80 mm [ORS9]						21	17 (PL) /20	063 (CZ-SK	()					

^{*}DIMENSIONS OF THE WALL OPENING FOR THE VERSION WITHOUT A DOOR FRAME SHOULD BE IDENTICAL TO THE INTERNAL WIDTH OF THE DOOR FRAME.





AVAILABLE DOOR FRAMES

[ORS3] adjustable door frame with a flat angle architrave 60 mm-wide

price includes: adjustable door frame with a flat angle architrave 60 mm-wide, with milling and swing sheet for a hook lock

[ORS9] adjustable door frame with a flat angle architrave 80 mm-wide

price includes: adjustable door frame with a flat angle architrave 80 mm-wide, with milling and swing sheet for a hook lock

CLASSIFICATION OF RAILS AND RAIL COVERS DEPENDING ON THE WIDTH OF THE SLIDING SYSTEM

door leaf	length of rail cover	number of rail cover el.	number of rails and angle architraves
"60"	1350 mm		
"70"	1550 mm		1 rail and angle architrave
"80"	1750 mm	1 element	200 cm-long
"90"	1950 mm		
"100"	2150 mm		2 rails and angle
"60"+"60"	2600 mm	2 -1	architraves
"60"+"70"	2800 mm	2 elements	200 cm-long

door leaf	length of rail cover	number of rail cover el.	number of rails and angle architraves	
"70" + "70" lub "60" + "80"	3000 mm			
"70" + "80" lub "60" + "90"	3200 mm			
"80" + "80" lub "70" + "90" lub "60" + "100"	3400 mm		2 rails and angle architraves	
"80"+"90" lub "70"+"100"	3600 mm	2 elements	200 cm-long	
"90"+"90"lub"80"+"100"	3800 mm			
"90"+"100"	4000 mm			
"100"+"100"	4200 mm		3 rails and angle architraves 200 cm-long	



rail cover A—91.5 mm [ORS3] or 111.5 mm [ORS9]; B—92 mm



bumper




soft-close hardware for sliding door



strike plate

Technical information

DIMENSIONS OF REBATED, NON-REBATED AND SLIDING DOORS



	"60"	"70"	"80"	"90"	"100"					
А	618	718	818	918	1018					
В	644	744	844	944	1044					
C	C 2027 (PL) / 1975 (CZ-SK)									
D	2040 (PL) / 1988 (CZ-SK)									
	Dimensions A and C are outer dimensions of non-rebated doors; Dimensions B and D are outer dimensions of rebated doors and doors prepared for sliding systems.									

A REBATE AND A COUNTER-REBATE IN DOUBLE DOOR LEAVES



MODULAR AND FLAT REBATED DOORS WITH A BLOCK OR ADJUSTABLE DOOR FRAME

DOUBLE DOOR LEAVES WITH A REBATE AND A COUNTER-REBATE



NON-REBATED DOORS WITH AN ADJUSTABLE DOOR FRAME

DOUBLE DOOR LEAVES WITH A REBATE AND A COUNTER-REBATE

ROUNDED VERTICAL AND UPPER EDGES IN DOOR LEAVES

	SW	ING	CLIDING SYSTEMS	EDGE FROM THE CONTACT		
	REBATED	NON-REBATED	SLIDING SYSTEMS	SIDE OF DOUBLE DOOR		
MODULAR DOORS	YES	YES	YES	YES		
FLAT DOORS	YES	_	NO	NO		
MILLED DOORS						
HOME LINE						
OPTIMO LINE	NO	NO	NO	NO		
ARTEO						
VETRA						
FOLDING DOORS	YES*	_	-	_		
* OUTER VERTICAL EDGES	ONLY.					



VENTILATION

According to the norm, the door to the bathroom, shower, and separate WC should open outwards, have a passage width of at least 0.8 m and height of 2 m, and have ventilation holes for the air supply in the bottom of the door with total ventilation area of at least 0.022 m². The total ventilation area is the sum of the gap under the door (standard 7 mm) and additional solutions that increase the total net ventilation area such as ventilation sleeves, ventilation undercut, and ventilation grid. The use of a ventilation grid ensures the correct ventilation area for all door widths, while using the sleeve and/or undercut the increased gap between the door and the floor should be used to meet the required regulations. If the regulations mentioned above must be obliged, the clients must trim the door on their own.



VENTILATION UNDERCUT (visualization for door leaf width "80")





RECUPERATION





VENTILATION SLEEVES (visualization for door leaf width "80")





VENTILATION GRID (visualization for door leaf width "80")



door width	number of ven- tilation sleeves	door leaf with metal ventilation sleeves total ventilation area:	door leaf with PVC ventilation sleeves for foiled doors ventilation sleeves and the g	door leaf with PVC ventilation sleeves for modular doors gap under the door (7 mm) [m²]	total ventilation area: ventilation undercut and the gap under the door (7 mm) [m²]	total ventilation area: ventilation grid and the gap under the door (7 mm) [m²]
"60"	3	0.0069	0.0062	0.0056	0.00835	
"70"	4	0.0085	0.0075	0.0067	0.01085	
"80"	5	0.0101	0.0089	0.0079	0.01335	. 0.022
"90"	6	0.0117	0.0103	0.0090	0.01585	> 0.022
"100"	6	0.0124	0.0110	0.0097	0.01835	
"110"	6	0.0131	0.0117	0.0104	0.02085	

NOTE: D'ARTAGNAN, ARTEO AND VETRA DOOR LEAVES CANNOT BE FITTED WITH SLEEVES, UNDERCUTS OR VENTILATION GRIDS. SLIDING DOORS MEET THE VENTILATION REQUIREMENT DUE TO THE DESIGN OF THE SYSTEM. INVADO DOES NOT MAKE SEVERAL VENTILATION SOLUTIONS AT THE SAME TIME.

GUIDELINES FOR BUILDINGS EQUIPPED WITH A RECUPERATION SYSTEM

To ensure adequate airflow from the living areas to the corridor, sanitary, and auxiliary rooms, it is recommended that all internal doors should have a gap at the bottom. The gap area in doors in living and auxiliary rooms should be at least 80 cm2 (INVADO doors with an undercut fully meet this requirement). The size of the ventilation gap in doors in sanitary rooms should be 200 cm².

Block door frame

FOR REBATED DOORS [OB3]



CONSTRUCTION

- MDF board
- foiling—all decors available in the INVADO offer
- cross-section: 90 x 44 mm

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "110"
- width of double doors "120" to "200"

OPTIONS AT EXTRA CHARGE FOR BLOCK DOOR FRAMES

- flat architrave LO1 60 x 10 mm "60"-"110"
- flat architrave LO7 80 x 16 mm "60"—"110"
- quadrant LC1 (single doors) or LC2 (double doors)
- door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- door frames for double doors
- additional hinge in door frame "60"-"80"










DIMENSIONS

	width of single doors (mm)							width of double doors (mm)								
		"60"	"70"	"80"	"90"	"100"	"110"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf	644	744	844	944	1044	1144	1278	1378	1478	1578	1678	1778	1878	1978	2078
s2	width of the wall opening	718	818	918	1018	1118	1218	1354	1454	1554	1654	1754	1854	1954	2054	2154
s3	out er width of the door frame	688	788	888	988	1088	1188	1324	1424	1524	1624	1724	1824	1924	2024	2124
s4	internal width of the door frame	600	700	800	900	1000	1100	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1 door leaf height								2040 (I	PL) /1988 (CZ-SK)						
h2	h2 height of the wall opening							2084 (I	PL) /2030 (CZ-SK)						
h3	outer height of the door frame							2069 (I	PL) /2015 (CZ-SK)						
h4	internal height of the door frame							2025 (I	PL) /1971 (CZ-SK)						






APPLICATION OF QUADRANT LC2 AND ARCHITRAVE LO1, AND THEIR COVERING SURFACES



Adjustable door frame

FOR REBATED DOORS [ORS1/ORS8]







CONSTRUCTION

- MDF board
- foiling—all decors available in the INVADO offer
- A set of 45° jointed angle brackets is included as standard with the door frame.
 Thestandard angle bracket consists of a flat architrave, available in 60 mm or 80 mm widths, and a 30 mm long tongue. Additionally, a separate 50 mm long angle bracket with a tongue set can be ordered (see extra charges below).

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "110"
- width of double doors "120" to "200"

OPTIONS AT EXTRA CHARGE

- door frames with sidelights and transoms (without glass) with circumference up to 5 l.m
- door frames for double doors
- additional hinge in door frame "60"—"80"
- standard angle architrave (a "tongue" 30 mm-long, an architrave 60 or 80 mm-wide)
- angle architrave with longer "tongue" (a "tongue" 50 mm long, an architrave 60 or 80 mm-wide)
- wall framing ("blind door frame")




NOMINAL COVERAGE OF THE WALL


symbol	А	В	С	D	Е	F	G	Н	I	J	
wall thickness	75–94	95–114	120–139	140–159	160–179	180–199	200–219	220–239	240–259	260–279	
symbol	K	L	M	N	0	Р	Q	R	S	Т	U



DIMENSIONS

				wid	th of sing	le doors (r	nm)					width of	double do	oors (mm)			
			"60"	"70"	"80"	"90"	"100"	"110"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1		door leaf width	644	744	844	944	1044	1144	1278	1378	1478	1578	1678	1778	1878	1978	2078
s2	width o	f the wall opening	674	774	874	974	1074	1174	1310	1410	1510	1610	1710	1810	1910	2010	2110
s3	outer width	of the door frame	644	744	844	944	1044	1144	1280	1380	1480	1580	1680	1780	1880	1980	2080
s4	internal width	of the door frame	600	700	800	900	1000	1100	1236	1336	1436	1536	1636	1736	1836	1936	2036
s5	width of the	60 mm [ORS1]	744	844	944	1044	1144	1244	1380	1480	1580	1680	1780	1880	1980	2080	2180
55	architraves	80 mm [ORS8]	784	884	984	1084	1184	1284	1420	1520	1620	1720	1820	1920	2020	2120	2220
h1		door leaf height							2040 (P	L) /1988 (0	CZ-SK)						
h2	heig	ht of wall opening							2062 (P	L) /2008 (0	CZ-SK)						
h3	outer height	of the door frame							2047 (P	L) /1993 ((CZ-SK)						
h4	internal height	nal height of the door frame							2025 (PL)/1971 (CZ-SK)								
h5	height of the	60 mm [ORS1]							2097 (P	L) /2043 (0	CZ-SK)						
115	architraves	80 mm [ORS8]							2117 (P	L) /2063 (0	CZ-SK)						





WALL THICKNESS RANGE



DOOR FRAME WIDTH MODIFICATION The adjustable door frame is made in dimensions adjustable to the wall thickness in steps of 20 mm. The minimum wall thickness is 75 mm.

NOTE: due to special mills, there is a possibility to trim the frame and reduce the wall thickness coverage by 15 mm. Door frame for wall thickness greater than 360 mm consists of at least two connected components.



Adjustable door frame

FOR NON-REBATED DOORS [ORS7/ORS10/ORS4]



CONSTRUCTION

- MDF board
- foiling—all decors available in the INVADO offer
- A set of 45° [ORS7] and [ORS10] or 90° [ORS4] jointed angle brackets is included
 as standard with the door frame. The standard angle bracket consists of a flat
 architrave, available in 60 mm or 80 mm widths, and a 30 mm long tongue.
 Additionally, a separate 50 mm long angle bracket with a tongue set can be
 ordered (see extra charges below).

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "110"
- width of double doors "120" to "200"

OPTIONS AT EXTRA CHARGE

- door frames with sidelights and transoms (without glass) with circumference up to 5 lm
- door frames for double doors
- additional hinge in door frame
- standard angle architrave (a "tongue" 30 mm-long, an architrave 60 or 80 mm-wide)
- angle architrave with longer "tongue" (a "tongue" 50 mm long, an architrave 60 or 80 mm-wide)






NOMINAL COVERAGE OF THE WALL


symbol	А	В	С	D	Е	F	G	Н	1	J	
wall thickness	75–94	95–114	120–139	140–159	160–179	180–199	200–219	220–239	240-259	260-	-279
symbol	К	L	M	N	0	Р	Q	R	S	Т	U
wall thickness	280–299	300–319	320–339	340–359	360–379	380–399	400–419	420–439	440–459	460–479	480–499*



DIMENSIONS

				wid	th of sing	le doors (r	nm)					width of	double do	oors (mm)			
			"60"	"70"	"80"	"90"	"100"	"110"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1		door leaf width	618	718	818	918	1018	1118	1239	1339	1439	1539	1639	1739	1839	1939	2039
s2	width o	f the wall opening	674	774	874	974	1074	1174	1294	1394	1494	1594	1694	1794	1894	1994	2094
s3	outer width	of the door frame	644	744	844	944	1044	1144	1264	1364	1464	1564	1664	1764	1864	1964	2064
s4	internal width	of the door frame	600	700	800	900	1000	1100	1220	1320	1420	1520	1620	1720	1820	1920	2020
	width of the	60 mm [ORS7]	744	844	944	1044	1144	1244	1364	1464	1564	1664	1764	1864	1964	2064	2164
s5	door frame with architraves	80 mm [ORS10]	784	884	984	1084	1104	1284	1404	1504	1604	1704	1804	1904	2004	2104	2204
		80 mm [ORS4]		004	904		1184	1204	1404	1304	1004	1704	1004	1904	2004	2104	2204
h1		door leaf height							2027 (F	PL) /1975 (CZ-SK)						
h2	heig	ht of wall opening							2062 (F	PL)/2008 (CZ-SK)						
h3	outer height	of the door frame							2047 (F	PL) /1993 (CZ-SK)						
h4	internal height	of the door frame							2025 (F	PL) /1971 (CZ-SK)						
	height of the	60 mm [ORS7]							2097 (F	PL) /2043 (CZ-SK)						
h5	door frame with	80 mm [ORS10]							2117/	N /2062 /	C7 (V)						
	architraves	80 mm [ORS4]							Z11/ (I	PL)/2063 (CZ-SK)						





WALL THICKNESS RANGE



DOOR FRAME RANGE ADJUSTMENT The adjustable door frame is available in sizes that accommodate wall thicknesses in 20 mm increments. The minimum wall thickness is 75 mm.


NOTE: For a wall thickness of 75-85, a frame with dimension A (75-94) must be used. In this case, the angle must be shortened at the milling point — otherwise the frame will not sit flush with the wall on both sides. A door frame for a wall thickness of 360 mm and above consists of at least two interconnected components.




Metal door frames

[FD 11 / FD 12 / FD 14 / FD 61-67]

METAL DOOR FRAME [FD 11/FD 12]





CONSTRUCTION

- welded frame
- ungalvanized plate with a thickness of 1.2 mm
- powder-coated frame in a choice of standard RAL colours
- 2 silver hinges and a seal included
- universal mounting brackets for brick walls and plasterboard walls

RANGES OF WALL THICKNESS COVERING

- door frame FD 11—75 mm
- door frame FD 12—100 mm

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "110"
- width of double doors "120" to "200"

DIMENSIONS

	single door (mm)								double door (mm)								
		"60"	"70"	"80"	"90"	"100"	"110"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"	
s1	door leaf width	644	744	844	944	1044	1144	1278	1378	1478	1578	1678	1778	1878	1978	2078	
s2	width of the wall opening	680	780	880	980	1080	1180	1316	1416	1516	1616	1716	1816	1916	2016	2116	
s3	outer width of the door frame	696	796	896	996	1096	1196	1332	1432	1532	1632	1732	1832	1932	2032	2132	
s4	internal width of the door frame	600	700	800	900	1000	1100	1236	1336	1436	1536	1636	1736	1836	1936	2036	
h1	door leaf height								2040								
h2	height of the wall opening								2065								
h3	outer height of the door frame								2072								
h4	internal height of the door frame								2024								

AVAILABLE RAL DECORS




OPTIONS AT EXTRA CHARGE


- third hinge
- reinforcement for the self-closer
- adapted for the electric door strike



METAL DOOR FRAME (SMALL) [FD 14]







CONSTRUCTION

- · welded frame
- ungalvanized plate with a thickness of 1.2 mm
- powder-coated frame in a choice of standard RAL colours
- 2 silver hinges and a seal included
- universal mounting brackets for brick walls and plasterboard walls

DOOR FRAME FOR DOOR LEAVES IN WIDTH


- width of single doors "60" to "110"
- width of double doors "120" to "200"


DIMENSIONS

			sii	ngle door	(mm) (mr	n)					dou	ble door (i	mm)			
		"60"	"70"	"80"	"90"	"100"	"110"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1144	1278	1378	1478	1578	1678	1778	1878	1978	2078
s2	width of the wall opening	671	771	871	971	1071	1171	1307	1407	1507	1607	1707	1807	1907	2007	2107
s3	outer width of the door frame	696	796	896	996	1096	1196	1332	1432	1532	1632	1732	1832	1932	2032	2132
s4	internal width of the door frame	600	700	800	900	1000	1100	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1	door leaf height								2040							
h2	height of the wall opening								2043							
h3	outer height of the door frame								2072							
h4	internal height of the door frame								2024							

ADJUSTABLE METAL DOOR FRAME [FD 61-67]







CONSTRUCTION

- 2-part frame, adjustable (adjustment range in 30 mm steps)
- ungalvanized plate with a thickness of 1.5 mm
- powder-coated frame in a choice of standard RAL colours
- 2 silver hinges and a seal included
- universal mounting brackets for brick walls and plasterboard walls

DOOR FRAME FOR DOOR LEAVES IN WIDTH

- width of single doors "60" to "110"
- width of double doors "120" to "200"

DIMENSIONS

			single do	oor (mm)			double door (mm)									
		"60"	"70"	"80"	"90"	"100"	"110"	"120"	"130"	"140"	"150"	"160"	"170"	"180"	"190"	"200"
s1	door leaf width	644	744	844	944	1044	1144	1278	1378	1478	1578	1678	1778	1878	1978	2078
s2	width of the wall opening	693	793	893	993	1093	1193	1326	1426	1526	1626	1726	1826	1926	2026	2126
s3	outer width of the door frame	716	816	916	1016	1116	1216	1350	1450	1550	1650	1750	1850	1950	2050	2150
s4	internal width of the door frame	600	700	800	900	1000	1100	1236	1336	1436	1536	1636	1736	1836	1936	2036
h1	door leaf height								2040							
h2	height of the wall opening								2070							
h3	outer height of the door frame								2082							
h4	internal height of the door frame								2024							

Concealed door frame SARA-PRO





SARA PRO prepared for painting and wallpapering

The SARA-PRO door frame introduces a brand new quality in interior decoration. Invisible to the naked eye, it makes the area lighter. Ideal for minimalist and modern interiors. Available in outer and inner versions.

Non-rebated door leaf for outer door frame and rebated door leaf for inner door frame is based on the NORMA DECOR 1 door leaf.

DECORS





CONSTRUCTION

- the frame is made of an MDF board
- (STANDARD) stabilisation filling—"honeycomb"
- (OPTIONAL) stabilisation filling—tubular chipboard
- frame with filling faced with HDF board on both sides
- (OPTIONAL) leaf prepared for painting and wallpapering
- (OPTIONAL) leaf covered with ENDURO or CPL 0.15 mm foil
- width of single doors "60"-"90"

STANDARD EQUIPMENT

- 2 hidden hinges
- magnetic lock for a standard key, a WC knob or a cylinder lock insert or door without a keyhole

ADDITIONAL OPTIONS

door without a keyhole

filling—tubular chipboard

ventilation undercut

PVC ventilation sleeves


ventilation grid


cylinder lock insert 31/36

DIMENSIONS OF A DOOR LEAF AND CONCEALED DOOR FRAME

			inner door	frame (mm)		outer door frame (mm)					
		"60"	"70"	"80"	"90"	"60"	"70"	"80"	"90"		
s1	door leaf width	618	718	818	918	618	718	818	918		
s2	width of the wall opening	698	798	898	998	698	798	898	998		
s3	outer width of the door frame	688	788	888	988	688	788	888	988		
s4	internal width of the door frame	603	703	803	903	603	703	803	903		
h1	door leaf height		2027 (PL) /1	975 (CZ-SK)		2017 (PL) /1965 (CZ-SK)					
h2	height of the wall opening		2076 (PL) /2	024 (CZ-SK)			2066 (PL) /2	014 (CZ-SK)			
h3	outer height of the door frame		2069 (PL) /2	017 (CZ-SK)		2059 (PL) /2007 (CZ-SK)					
h4	internal height of the door frame		2027 (PL) /1	975 (CZ-SK)		2017 (PL) /1965 (CZ-SK)					

CONCEALED DOOR FRAME SARA-PRO-INNER






Housing system

FOR METAL DOOR FRAMES [ORS5]





- A door frame housing
- aluminium angle element
- B metal door frame
- gasket

FEATURES

The ORS5 metal frame cover is an adjustable overlay frame that allows for the installation of a new door leaf and adjustable frame without removing the existing metal frame. By covering the old frame, it enables the use of standard INVADO door leaves. NOTE: the ORS5 frame changes the position of the leaf in relation to the wall run.

WIDTH OF THE DOOR FRAME FOR DOOR LEAVES

width of single doors "60" to "90"

RANGES OF WALL THICKNESS


60-94, 95-129, 130-199, 200-269


INTERNAL DIMENSIONS OF METAL DOOR FRAME (MM)


		"60"	"70"	"80"	"90"		
s1	door leaf width	600	700	800	900		
s2	clear width of the enclosure	573	673	773	873		
h1	door leaf height	2025 (PL)/1975 (CZ-SK)					
h2	clear height of enclosure	2011					

Housing system for metal door frames for walls thicker than 130 mm has an additional enlarging element.

For the range of 130–199—the enlarging element is 85 mm-wide. For the range of 200–269—the enlarging element is 155 mm-wide.









Accessories

FOILED AND MODULAR DOORS



caps for hinges (white, satin chrome, chrome, black, gold) Set for 1 piece of hinge



hinge Set with leaf and frame hinge



hidden hinge Delivered with a door frame



cylinder lock insert



porthole (black or silver with satinated or transparent glass) Included in the price of the door Norma Decor 6 and Optimo Line 6



automatic bottom door seal



aluminium threshold



door seal (black, white, gray, brown, beige)



 $\begin{array}{c} \textbf{ventilation sleeves} \\ \textbf{PVC} \end{array}$



ventilation sleeves metal round



ventilation sleeves metal square



ventilation grid

BLACK IRONMONGERY FOR REBATED DOORS



black hinge (rebated doors) Set with leaf and frame hinge



black lock (key/WC/cylinder insert)



strike plate for the block door frame



strike plate for the adjustable door frame



OPTIMO LINE







magnetic lock



hidden hinges

Colours: white, satin chrome, gold, black

Surcharge for changing the colour of the fittings—set: 2 hinges + strike plate + door leaf lock



edge band in a different colour than the door leaf surface (natural hamilton oak, alpine white or pure black)

SLIDING SYSTEMS



hook lock WC/key

grip with



folding key and a thimble



grip with WC knob and a thimble



Colours: chrome, satin chrome, gold, black



grip and a thimble



strike plate



bumper



soft-close hardware for sliding door

KICK AND PUSH METAL PANELS

- material: polished stainless stee
- dimensions: width matched to the door leaf, height 300 mm, thickness 0.6 mm
- price per set for two sides of the leaf



PUSH top panel with handle holes



standard KICK bottom panel



bottom panel with undercut (undercut – height: 15 mm)



bottom panel with holes for sleeves* (ventilation sleeves – ø 40 mm)



KICK bottom panel with ventilation grid (grid dimensions: 430 x 110 mm)

(depending on the width of the leaf a different number of ventilation sleeves is used: "60" – 3 sleeves / "70" – 4 sleeves / "80" – 5 sleeves / "90"-"110" – 6 sleeves)

^{*} ventilation sleeves – diameter: 40 mm

Handles

IBIZA K



with escutcheon for cylinder lock insert



white

black








with escutcheon for repeatable key



with escutcheon for cylinder lock insert





TOPAZ









with escutcheon for WC lock



stainless steel (inox)



FOSTER-BI



with escutcheon for repeatable key





with escutcheon for WC lock

white matt nickel glossy chrome black

glossy gold

SPARK FIT





with escutcheon for repeatable key



with escutcheon for cylinder lock insert

with escutcheon for cylinder lock insert



with escutcheon for WC lock





GIUSSY





with escutcheon for repeatable key



with escutcheon for cylinder lock insert



with escutcheon for WC lock



nickel/chrome



brown grafiatto

INVADO





with escutcheon for repeatable key



with escutcheon for cylinder lock insert



with escutcheon for WC lock



nickel/chrome

PRESTO





with escutcheon for repeatable key



with escutcheon for cylinder lock insert



with escutcheon for WC lock



nickel/chrome

UNO-R





with escutcheon for repeatable key



with escutcheon for cylinder lock insert



with escutcheon for WC lock



stainless steel (inox)

UNO





with escutcheon for repeatable key



with escutcheon for cylinder lock insert



with escutcheon for WC lock




stainless steel (inox)





















clips—30 pcs/package

CLIPS

FINISHING ELEMENT

NOTE: THE LENGTH OF A SINGLE SKIRTING IS 2.4 M.
THE SKIRTINGS ARE PACKED AND SOLD IN SETS OF 5.



INVADO Ltd. Dzielna, st. Leśna 2 42-793 Ciasna, Poland

e-mail: biuro@invado.pl tel. +48 34 351 05 40



EXPORT MANAGERS

DIRECTOR

+ 48 34 35 10 550 + 48 508 052 407

+ 48 34 35 13 882

+ 48 513 120 072

+ 48 34 35 10 549 + 48 509 680 283

+ 48 34 35 13 843 + 48 518 821 019

+ 48 34 35 13 878

+ 48 503 186 762

A company of Arbonia Group

ARBONIA 🕸

DISTRIBUTOR'S STAMP:

All information in the catalogue do not constitute an offer within the meaning of the Civil Code and are published for informational purposes only. Manufacturer reserves the right to make changes.

Note! Due to the printing technique the colors of the products presented in the catalogue may differ from the original. All rights reserved. Copying and publication of this catalogue on web sites and in other media without the written consent from INVADO Sp. z o.o. is prohibited.



